



WWW.NAMATIRE.US | PCR CATALOGUE

MASSE 567

SUV HT

NAMA



- The shorter braking distance for safe driving on wet road conditions. Improved tread groove enhance water evacuation performance.
- The strong tire casing structure provides better load capacity. Closed shoulder pattern design effectively increasing shoulder strength and tread surface contact against the road, which benefit for stable handling and durability by using a good durability compound bring longer tire life.
- Central straight grooves and two Zig-Zag lateral grooves provide quick water drainage and enhance great wet safety performance and anti-irregular wear.

Wheel Dia.	Size	L/S	LR	rr	Wet grip	Sound	UTQG
15	235/75R15 XL	T	109	E	C	69	420 A A
	235/75R15	T	105	E	C	69	420 A A
16	205/60R16 XL	H	96	E	C	69	420 A A
	205/60R16	H	92	E	C	69	420 A A
	215/60R16	H	95	E	C	69	420 A A
	215/60R16 XL	H	99	E	C	69	420 A A
	215/65R16	H	98	E	C	69	420 A A

MASSE 567

SUV HT

NAMA



Wheel Dia.

Size

L/S

LR

rr

Wet grip

Sound

UTQG

16

215/70R16	H	100	E	C	69	420 A A
225/60R16 XL	T	102	E	C	69	420 A A
225/70R16	H	103	E	C	69	420 A A
235/60R16	H	100	E	C	69	420 A A
235/70R16	T	106	E	C	69	420 A A
245/70R16 XL	T	111	E	C	69	420 A A
245/75R16	H	111	E	C	69	420 A A
255/70R16	T	111	E	C	70	420 A A
265/70R16	T	112	E	B	72	420 A A
275/70R16	T	114	E	B	72	420 A A

17

235/55R17 XL	V	103	E	B	69	420 A A
215/60R17	H	96	E	B	69	420 A A
225/60R17	H	99	E	B	69	420 A A
225/65R17	H	102	E	B	69	420 A A

MASSE 567

SUV HT

NAMA



Wheel Dia.

Size

L/S

LR

rr

Wet grip

Sound

UTQG

17

235/65R17	V	104	E	B	69	420 A A
245/65R17 XL	T	111	E	B	69	420 A A
265/65R17	T	112	E	B	72	420 A A
265/70R17	T	115	E	B	72	420 A A

18

215/55R18	V	95	E	B	69	420 A A
225/60R18	H	100	E	B	69	420 A A
235/55R18 XL	V	104	E	B	69	420 A A
235/60R18	H	103	E	B	69	420 A A
255/55R18 XL	V	109	E	B	69	420 A A
255/60R18 XL	H	112	E	B	69	420 A A
265/60R18 XL	H	114	E	B	73	420 A A
265/70R18	H	116	E	B	72	420 A A
275/65R18	T	116	E	B	72	420 A A
285/60R18	H	116	E	B	73	420 A A

MASSE 567

SUV HT

NAMA



Wheel Dia.	Size	L/S	LR	rr	Wet grip	Sound	UTQG
19	245/55R19	H	103	E	B	69	420 A A
	235/55R19	V	101	E	B	69	420 A A
20	275/45R20 XL	V	110	E	B	73	420 A A
	275/60R20	H	115	E	B	72	420 A A
	285/50R20 XL	V	116	E	B	73	420 A A
	285/45R22 XL	V	114	E	B	73	420 A A

MASSE 563

MT/A*4

NAMA



- The powerful profile design provides superior driving performance and grip capability. Skid resistance ensures outstanding performance in mud and unpaved road.
- Open shoulder design provides a more powerful grip and traction.
- Evenly distributed grooves provide excellent wet driving performance and braking performance.
- The leading anti-wear compound reduces wear and longer life span.

Wheel Dia.	Size	L/S	LR	PLY
15	30×9.50R15LT	104	Q	6/C
	31*10.50R15LT	109	Q	6/C
	32×11.50R15LT	113	Q	6/C
	LT235/75R15	104/101	S	6/C
16	LT245/75R16	108/104	Q	6/C
	LT265/70R16	117/114	Q	8/D
	LT265/75R16	123/120	Q	10/E

MASSE 563

MT/A*4

NAMA



Wheel Dia.	Size	L/S	LR	PLY
17	35×12.50R17LT	121	Q	10/E
	LT265/70R17	121/118	Q	10/E
	LT285/70R17	121/118	R	10/E
	LT295/70R17	121/118	Q	10/E
18	33×12.50R18LT	118	Q	10/E
	35×12.50R18LT	118	Q	8/D
	LT285/65R18	125/122	Q	10/E
20	33×12.50R20LT	114	Q	10/E
	35×12.50R20LT	121	Q	10/E
	LT275/65R20	126/123	Q	10/E
22	33×12.50R22LT	109	Q	10/E
	35×12.50R22LT	117	Q	10/E
	37×13.50R22LT	123	K	10/E



***INNOVATION
AT EVERY TURN***